


S&S LEASING, L.C.  
CC#96-R0082198 R.P.R.  
ZONED LI  
RATLIFF MASONRY ADDITION  
LOT 1, BLOCK A  
1.650 ACRES

CONTRACTOR TO INSTALL 4" MH  
EXIST. 8" STUBOUT FL 508.45  
6" SERVICE LINE TO BLOC. w/  
CLEANOUT AS SHOWN

40' X 50' COMMON  
ACCESS EASEMENT

ZONED LI  
LOT 2, BLOCK A



"AS-BUILT"  
RECORD DRAWING


THE INFORMATION SHOWN ON THESE PLANS HAS BEEN REVISED TO REFLECT CHANGES TO PUBLIC IMPROVEMENTS MADE DURING CONSTRUCTION PROVIDED TO ENGINEER BY THE CONTRACTOR UNLESS OTHERWISE NOTED. THE CONSTRUCTION OF THE PUBLIC IMPROVEMENTS IS IN GENERAL CONFORMANCE WITH THESE PLANS BASED UPON INFORMATION PROVIDED BY THE CONTRACTOR, AND THE RESPONSIBILITY FOR ACCURACY AND COMPLETENESS BELONGS TO THE CONTRACTOR.

*Robert D. Pettit*  
PETTIT & ASSOCIATES

DATE: 4-10-2000

CONTRACTOR TO VERIFY  
EXIST. OR INSTALL 12" x 1" TAP  
& 2-3/4" MH'S w/APPROVED  
OCVA (DOMESTIC & IRRIGATION)

DELTA 20°24'49"  
R= 362.00'  
L= 128.97'  
CHORD BEARING= N 62°39'34" E  
CHORD LENGTH= 128.29'



DETAIL "A"  
NTS



S & S LEASING, L.C.  
CC# 96-R0082198 R.P.R.  
ZONED LI  
LOT 5, BLOCK A  
VALLEY RIDGE BUSINESS PARK EAST  
CAB. F. PG. 281 P.R.D.C.T.


LEGEND

— WATER LINE  
— SEWER LINE  
— EX. STORM SEWER  
— EASEMENT  
— CLEANOUT  
°c.a.

FIRE LANE STRIPING SPECIFICATIONS AND REQUIREMENTS

The access roadway and/or fire lane shall be striped on a paved surface, and be clearly marked on the pavement with a "red" line at least four (4) inches wide. "NO PARKING" and "FIRE LANE" in not less than four (4) inch letters in "white" shall be placed every other fifteen (15) feet on the strip. Where the fire lane is adjacent to a curb, the entire curb shall be painted. A legend stating "NO PARKING - FIRE LANE" of a minimum eighteen (18) inches painted in "yellow" shall be placed at all entrances to the fire lane (lettering may be larger, but 18" is minimum). All fire lanes shall connect at both ends to a dedicated street or be constructed with turn-around areas at the dead-end with a minimum radius of fifty (50) feet. All paint referred to shall be a traffic marking paint. When required during construction or other temporary use, approved signs shall be provided and maintained for fire apparatus access roads to identify such roads and prohibit the obstruction thereof of both. Signs must be secured so that they cannot be moved until permanent fire lane is painted.

O.I. or PVC PIPE



BRASS SAADDLES WILL BE REQUIRED  
ON ALL SERVICE CONNECTIONS

TYPICAL SERVICE CONNECTION  
N.T.S.

ALL FITTINGS CORPORATIONS AND  
CURB STOPS TO BE COMPRESSION  
FITTING. FLARES WILL NOT BE ALLOWED

PROPERTY LINE

2'-0"  
Water Meter  
Easement

TO BLOC. SERVICE

\* METER BOX SHALL BE CENTERED  
WITHIN THE 2'-0" WATER  
METER EASEMENT

EXTEND COPPER SERVIC PIPE  
6" BEYOND PROPERTY LINE  
AND SET CURB STOP

CORPORATION STOP TO BE  
MUELLER OR APPROVED EQUAL